

## Oyster Shell Rigid Core Bamboo Flooring



### Specifications

<b>Item No</b>	300844149805	<b>Warranty</b>	Lifetime Structural and Finish (residential)
<b>Flooring group</b>	Click Lock BSPC	<b>R value</b>	
<b>Price</b>	4.26/sq ft	<b>Moisture content</b>	ASTM D4442, Oven Dry Method: 6%-10% average
<b>Species</b>	Strand Woven Bamboo with rigid SPC core	<b>SurfSlip resistance</b>	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59
<b>Sq ft/box</b>	15.45	<b>Flammability</b>	ASTM E648: Class 1 Interior
<b>Finish</b>	Accuseal Ultra with aluminum oxide	<b>Smoke density</b>	ASTM E622: Max 344 flaming, 192 non-flaming
<b>Surface</b>	handscraped	<b>Dimensional</b>	ASTM D1037 50/90% RH,
<b>Janka rating</b>	5342	<b>Stability</b>	Linear .03, Thickness 1.52, Width .20
<b>Grain</b>	Bamboo_SPC	<b>Coating adhesion</b>	Classification: 5B
<b>Sustainability</b>	Lacey Act Compliant.	<b>Acclimation period</b>	24 hours
<b>Nailing info</b>	do not nail	<b>Weight/box</b>	37
<b>Length</b>	3 ft (920 mm)	<b>Planks/box</b>	12
<b>Width</b>	5-1/8 in (130 mm)	<b>Radiant Heat Safe</b>	Yes
<b>Thickness</b>	9/32 in (7mm - includes 1mm acoustic pad)	<b>High traffic</b>	Yes
<b>Wear layer</b>	1 mm Strand Bamboo	<b>Pet friendly</b>	Yes
<b>Profile</b>	Click Lock	<b>Install below grade</b>	Yes
<b>Profile/edges</b>	micro bevel	<b>Floating installation</b>	Yes
<b>Planks Description</b>	Single length planks: all planks are same dimensions	<b>Installation</b>	Floating

