

Schooner Keel Rigid Core Flooring



Specfications

Item No	300844149836		
Flooring group	Click Lock BSPC		
Price	4.6/sq ft		
Species	Strand Woven Bamboo with rigid SPC core		
Sq ft/box	15.45		
Finish	Accuseal Ultra with aluminum oxide		
Surface	antiqued		
Janka rating	5342		
Grain	Bamboo_SPC		
Sustainability	Lacey Act Compliant.		
Nailing info	do not nail		
Length	3 ft (920 mm)		
Width	5-1/8 in (130 mm)		
Thickness	9/32 in (7mm - includes 1mm acoustic pad)		
Wear layer	1 mm Strand Bamboo		
Profile	Click Lock		
Profile/edges	micro bevel		
Planks Description	Single length planks: all planks are same dimensions		

Warranty	Lifetime Structural and Finish (residential)		
R value			
Moisture content	ASTM D4442, Oven Dry Method: 6%-10% average		
SurfSlip resistanceace	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59		
Flammability	ASTM E648: Class 1 Interior		
Smoke density	ASTM E622: Max 344 flaming, 192 non-flaming		
Dimensional	ASTM D1037 50/90% RH,		
Stability	Linear .03, Thickness 1.52, Width .20		
Coating adhesion	Classification: 5B		
Acclimation period	24 hours		
Weight/box	37		
Planks/box	12		
Radiant Heat Safe	Yes		
High traffic	Yes		
Pet friendly	Yes		
Install below grade	Yes		
Floating installation	Yes		
Installation	Floating		